

Lubricant Spray for Push-Fit Installation

Lubricant spray Poliran, an innovative product with a special formulation that was developed by the Poliran research and development team in order to facilitate the implementation of push-fit systems and by utilizing the knowledge and practical experience of specialists in this field.

This product, by creating appropriate lubrication, facilitates the installation of various types of plumbing and water supply pipes and fittings that have sealing rings, including push-fit systems.

The best type of lubricant for installing and installing building plumbing push-fit systems are those that do not have a petroleum base and simply create appropriate lubrication to facilitate the installation of push-fit systems and play no role in sealing the system during the test.

Features

- Easy to use due to spray design and production
- Creates sufficient lubrication for connecting push-fit systems
- No pipe and connection protrusion during water tightness test due to the lubricant dissolving in water
- Does not interfere with system sealing during testing
- Compatible with various rubber, polymeric, and metallic materials
- Compatible with various sealing rings
- Compatible with hands due to the presence of glycerin in the lubricant
- Efficient use of solution with minimal waste
- No need to touch pipes to spread the solution



POLIRAN Building, No. 17,
Zagros St., Arjantin Sq.,
Tehran, Iran
Postal Code : 1516643311
Tel : +98 21 88648843
export.dep@poliran.org
WhatsApp : +98 912 9465921



www.poliran.org